Serial No.: 10/679,452

Docket No.: 28951.5039 D6

IN THE CLAIMS:

1. - 7. (Canceled).

8. (Withdrawn) A compressor having a compressing mechanism incorporated in an

enclosed container, wherein a muffler is provided at a discharge part of compressed refrigerant,

and a communication path curved in a circumferential direction is provided in a discharge hole

of the muffler, a fine pipe is connected to an outside of the communication path, and a collector

is coupled to a leading end of the fine pipe.

9. (Currently Amended) A compressor having comprising a compressing mechanism

incorporated in an enclosed container, and a discharge pipe for discharging compressed

<u>refrigerant</u>, wherein a fine pipe inclined at 90° or less with the in a flowing direction of

refrigerant flow within the discharge pipe is branched off and connected to a the discharge pipe

for discharging compressed refrigerant, and a hollow collector is coupled to the leading end of

the fine pipe, and the fine pipe is coupled to a central portion of the side surface of the collector.

10. (Withdrawn) A compressor having a compressing mechanism incorporated in an

enclosed container, wherein a fine pipe inclined at 90° or less in a flowing direction of refrigerant

is connected to a discharge pipe for discharging compressed refrigerant, the fine pipe is

connected to an inlet of a collector, a filter is provided in the collector, a bypass pipe is coupled

2

Serial No.: 10/679,452

Docket No.: 28951.5039 D6

to other outlet of the collector, and a leading end of the bypass pipe is coupled with the discharge

pipe.

11. (Withdrawn) A compressor having a compressing mechanism incorporated in an

enclosed container, wherein the compressing mechanism includes a rotary shaft for transmitting

rotation, and an upper bearing and a lower bearing for supporting the rotary shaft, an oil feed

path for lubrication is provided in the upper bearing and the lower bearing, and a collector

inclined at an angle of 90° or less in a flowing direction of lubricating oil and closed at a leading

end is provided in the oil feed paths.

12. (Withdrawn) The compressor of claim 8, wherein a magnetic piece is disposed in the

collector.

13. (Withdrawn) The compressor of claim 8, wherein hydrofluorocarbon is used as

refrigerant, and a refrigerating machine oil compatible with the refrigerant is used.

14. - 15. (Canceled).

3